



42

42

POWER AMPLIFIER PENTODE

Heater	Coated Unipotential Cathode	
Voltage	6.3	a-c or d-c volts
Current	0.7	amp.
Maximum Overall Length		4-11/16"
Maximum Diameter		1-13/16"
Bulb		ST-14
Base		Medium 6-Pin
Pin 1-Heater		Pin 4-Grid
Pin 2-Plate		Pin 5-Cathode
Pin 3-Screen		Pin 6-Heater
BOTTOM VIEW		

For additional data, refer to Type 6F6; and to Types 6F6 and 2A5 for additional curves. ←

← Indicates a change.

APRIL 20, 1938

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

DATA

42



42


OPERATION CHARACTERISTICS TRIODE CONNECTION-CLASS AB OPERATION

$E_f = 6.3$ VOLTS

INPUT STAGE : CLASS A DRIVER-ONE TYPE 42 AS TRIODE
PLATE VOLTS = 250
SELF-BIAS RESISTOR = 650 OHMS
OUTPUT STAGE : CLASS AB-TWO TYPE 42'S AS TRIODES
ZERO-SIGNAL PLATE VOLTS = 350, FROM
SUPPLY HAVING RESISTANCE (R_b)
SHOWN IN TABLE
ZERO-SIGNAL BIAS VOLTS = VALUE FROM
GRID-BIAS RESISTOR (R_c) OF
730 OHMS
OUTPUT LOAD, PLATE TO PLATE = 10000 OHMS

CONDI- TION	CURVE	R_b Ohms	DRIVER STAGE		INTERSTAGE TRANSFORMER	
			Input-Signal Volts* (RMS)	Plate Load Ohms	Voltage Ratio Prim.:1/2 Sec.	Peak Power Efficiency - %
1	—	0	14	15600	1.29	76.7
2	---	500	14	17400	1.29	76.0
3		1000	14	17000	1.29	76.7

* For maximum output



MARCH 1, 1938

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY INC.

92C-4884